




SSCN5551GS6

High Frequency High Gain NPN Power BJT

➤ Features

VCB	VCE	VEB	IC
180V	160V	6V	600mA

➤ Pin configuration




➤ Description

This device is designed for general-purpose high-voltage amplifiers and gas discharge display drivers. It is ideal for medium power amplification and switching.

SOT-23

➤ Applications


- General-purpose high-voltage amplifiers
- Gas discharge display drivers
- Medium power amplification and switching



Circuit Diagram

➤ Ordering Information

Device	Package	Shipping
SSCN5551GS6	SOT-23	3000/Reel



Marking(Top View)


➤ Absolute Maximum Ratings($T_A=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	180	V
Collector- Emitter Voltage	V_{CEO}	160	V
Emitter-Base Voltage	V_{EBO}	6	V
Collector Current-Continuous	I_C	600	mA
Collector Power Dissipation	P_C	625	mW
Junction Temperature	T_J	150	$^\circ C$
Storage Temperature	T_{STG}	-55 to 150	$^\circ C$


➤ Electrical Characteristics ($T_A=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	BV_{CBO}	$I_C=0.1mA, I_E=0$	180			V
Collector-emitter Breakdown Voltage	BV_{CEO}	$I_C=1mA, I_B=0$	160			V
Emitter -Base Breakdown Voltage	BV_{EBO}	$I_E=0.1mA, I_C=0$	6			V
Collector Cutoff Current	I_{CBO}	$V_{CB}=120V, I_E=0$			0.05	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB}=4V, I_C=0$			0.05	μA
DC Current Gain	h_{FE}	$V_{CE}=5V, I_C=10mA$	100		300	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=50mA, I_B=5mA$			0.5	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=50mA, I_B=5mA$			1.0	V
Transition frequency	f_T	$V_{CE}=5V, I_C=10mA$ $f=30MHz$	100		300	MHz


➤ Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)




Collector Current vs. Base-Emitter Voltage




DC Current Gain vs. Collector Current




$V_{BE(sat)}$ vs. Collector Current



$V_{CE(sat)}$ vs. Collector Current





Power derating vs. Ambient temperature




Transition Frequency vs. Collector Current

- Package Information



DIM	Millimeters		
	Min.	Typ.	Max.
A	0.89	-	1.12
A1	0.01	-	0.10
A2	0.88	0.95	1.02
b	0.30	-	0.51
c	0.08	-	0.18
D	2.80	2.90	3.04
E	2.10	2.37	2.64
E1	1.20	1.30	1.40
e1		1.90	
e		0.95	
L	0.40	0.50	0.60
L1		0.55	
N		3	
θ	0°	-	8°

Recommended Pad outline(Unit: mm)



**DISCLAIMER**

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.