




SSCN9014GS6

NPN Switching Transistor

➤ Features

VCB	VCE	VEB	IC
50V	45V	5V	100mA

➤ Pin configuration




➤ Description

The NPN Transistor is designed for use in linear and switching applications. The device is housed in the SOT-23 package, which is designed for telephony and professional communication equipment.


SOT-23

➤ Applications

- General purpose switching and amplification
- Telephony and professional communication equipment



Circuit Diagram



Marking(Top View)

➤ Ordering Information

Device	Package	Shipping
SSCN9014GS6	SOT-23	3000/Reel


➤ Absolute Maximum Ratings($T_A=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	50	V
Collector- Emitter Voltage	V_{CEO}	45	V
Emitter-Base Voltage	V_{EBO}	5	V
Collector Current-Continuous	I_C	100	mA
Collector Power Dissipation	P_C	450	mW
Junction Temperature	T_J	150	$^\circ C$
Storage Temperature	T_{STG}	-55 to 150	$^\circ C$


➤ Electrical Characteristics ($T_A=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	BV_{CBO}	$I_C=100\mu A, I_E=0$	50			V
Collector-emitter Breakdown Voltage	BV_{CEO}	$I_C=0.1mA, I_B=0$	45			V
Emitter -Base Breakdown Voltage	BV_{EBO}	$I_E=100\mu A, I_C=0$	6			V
Collector Cutoff Current	I_{CBO}	$V_{CB}=50V, I_E=0$			0.1	μA
Collector Cutoff Current	I_{CEO}	$V_{CE}=35V, I_B=0$			1	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB}=3V, I_C=0$			0.1	μA
DC Current Gain	h_{FE}	$V_{CE}=5V, I_C=1mA$	60		700	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=100mA, I_B=5mA$			0.3	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=100mA, I_B=5mA$			1	V
Transition frequency	f_T	$V_{CE}=5V, I_C=10mA$ $f=30MHz$	150			MHz


➤ Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)




Collector Current vs. Base-Emitter Voltage




DC Current Gain vs. Collector Current




$V_{BE(sat)}$ vs. Collector Current



$V_{CE(sat)}$ vs. Collector Current




Power derating vs. Ambient temperature




Transition Frequency vs. Collector Current

- Package Information



DIM	Millimeters		
	Min.	Typ.	Max.
A	0.89	-	1.12
A1	0.01	-	0.10
A2	0.88	0.95	1.02
b	0.30	-	0.51
c	0.08	-	0.18
D	2.80	2.90	3.04
E	2.10	2.37	2.64
E1	1.20	1.30	1.40
e1		1.90	
e		0.95	
L	0.40	0.50	0.60
L1		0.55	
N		3	
θ	0°	-	8°

Recommended Pad outline(Unit: mm)



**DISCLAIMER**

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.