



## SSCP4403GS6

### PNP Switching Transistor

#### ➤ Features

VCB	VCE	VEB	IC
-40V	-40V	-5V	-600mA

#### ➤ Description

The PNP Transistor is designed for use in linear and switching applications. The device is housed in the SOT-23 package, which is designed for telephony and professional communication equipment.


#### ➤ Applications

- General purpose switching and amplification
- Telephony and professional communication equipment


#### ➤ Ordering Information

Device	Package	Shipping
SSCP4403GS6	SOT-23	3000/Reel


#### ➤ Pin configuration



**SOT-23**



**Circuit Diagram**



**Marking(Top View)**



➤ **Absolute Maximum Ratings**( $T_A=25^{\circ}\text{C}$  unless otherwise noted)


Parameter	Symbol	Value	Unit
Collector-Base Voltage	$V_{CB0}$	-40	V
Collector- Emitter Voltage	$V_{CEO}$	-40	V
Emitter-Base Voltage	$V_{EBO}$	-5	V
Collector Current-Continuous	$I_C$	-600	mA
Collector Power Dissipation	$P_C$	300	mW
Junction Temperature	$T_J$	150	$^{\circ}\text{C}$
Storage Temperature	$T_{STG}$	-55 to 150	$^{\circ}\text{C}$
Thermal resistance From junction to ambient	$R_{\theta JA}$	417	$^{\circ}\text{C}/\text{W}$

➤ **Electrical Characteristics** ( $T_A=25^{\circ}\text{C}$  unless otherwise noted)


Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$BV_{CB0}$	$I_C = -100\mu\text{A}, I_E = 0$	-40			V
Collector-emitter Breakdown Voltage	$BV_{CEO}$	$I_C = -1\text{mA}, I_B = 0$	-40			V
Emitter -Base Breakdown Voltage	$BV_{EBO}$	$I_E = -100\mu\text{A}, I_C = 0$	-5			V
Collector Cutoff Current	$I_{CBO}$	$V_{CB} = -35\text{V}, I_E = 0$			-0.1	$\mu\text{A}$
Collector Cutoff Current	$I_{CEX}$	$V_{CE} = -35\text{V}, V_{EB(off)} = -0.4\text{V}$			-0.1	$\mu\text{A}$
Emitter Cutoff Current	$I_{EBO}$	$V_{EB} = -4\text{V}, I_C = 0$			-0.1	$\mu\text{A}$
DC Current Gain	$h_{FE}$	$V_{CE} = -1\text{V}, I_C = -0.1\text{mA}$	30			
		$V_{CE} = -1\text{V}, I_C = -1\text{mA}$	60			
		$V_{CE} = -1\text{V}, I_C = -10\text{mA}$	100			
		$V_{CE} = -2\text{V}, I_C = -150\text{mA}$	100		300	
		$V_{CE} = -2\text{V}, I_C = -500\text{mA}$	20			
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -150\text{mA}, I_B = -15\text{mA}$			-0.40	V
		$I_C = -500\text{mA}, I_B = -50\text{mA}$			-0.75	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = -150\text{mA}, I_B = -15\text{mA}$			-0.95	V
		$I_C = -500\text{mA}, I_B = -50\text{mA}$			-1.3	V
Transition frequency	$f_T$	$V_{CE} = -10\text{V}, I_C = -20\text{mA}$ $f = 100\text{MHz}$	200			MHz
<b>Delay time</b>	$t_d$	$V_{CC} = -30\text{V}, V_{BE(off)} = -0.5\text{V},$ $I_C = -150\text{mA}, I_{B1} = -15\text{mA}$			15	ns
Rise time	$t_r$				20	ns
Storage time	$t_s$	$V_{CC} = -30\text{V}, I_C = -150\text{mA},$ $I_{B1} = I_{B2} = -15\text{mA}$			225	ns
Fall time	$t_f$				60	ns




➤ Typical Performance Characteristics ( $T_A=25^\circ\text{C}$  unless otherwise noted)




Collector Current vs. Collector-Emitter Voltage




DC Current Gain vs. Collector Current




Collector Current vs. Base-Emitter Voltage




Capacitance vs. Reverse Voltage




$V_{BE(sat)}$  vs. Collector Current



$V_{CE(sat)}$  vs. Collector Current





**Power derating vs. Ambient temperature**



**Transition Frequency vs. Collector Current**




## ● Package Information



DIM	Millimeters		
	Min.	Typ.	Max.
A	0.89	-	1.12
A1	0.01	-	0.10
A2	0.88	0.95	1.02
b	0.30	-	0.51
c	0.08	-	0.18
D	2.80	2.90	3.04
E	2.10	2.37	2.64
E1	1.20	1.30	1.40
e1	1.90		
e	0.95		
L	0.40	0.50	0.60
L1	0.55		
N	3		
θ	0°	-	8°

## Recommended Pad outline(Unit: mm)





## DISCLAIMER

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICIENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.