



SSC8635GN6

N and P-Channel Enhancement Mode Power MOSFET

➤ Features

N-Channel

V_{DS}	V_{GS}	$R_{DS(ON)}$ Typ.	I_D
30V	$\pm 20V$	6.2m Ω @10V	53A
		9m Ω @4V5	

P-Channel

V_{DS}	V_{GS}	$R_{DS(ON)}$ Typ.	I_D
-30V	$\pm 20V$	8m Ω @-10V	-50A
		10m Ω @-4V5	

➤ Description

The SSC8635GN6 uses advanced trench technology to provide excellent $R_{DS(ON)}$ and low gate charge. The complementary MOSFETs may be used to form a level shifted high side switch, and for a host of other applications.

100% UIS + ΔV_{DS} + R_g Tested!


➤ Applications

- PWM Applications
- Load Switch
- DC-DC Converters
- Wireless Chargers



➤ Ordering Information

Device	Package	Shipping
SSC8635GN6	PDFN5X6-8L	5000/Reel


➤ Pin configuration



PDFN5X6-8L



Pin Configuration (Top View)



Marking

(XXYY: Internal Traceability Code)



➤ Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	N-Channel	P-Channel	Unit	
V_{DSS}	Drain-to-Source Voltage	30	-30	V	
V_{GSS}	Gate-to-Source Voltage	± 20	± 20	V	
I_D	Continuous Drain Current ^d	$T_C=25^{\circ}\text{C}$	53	-50	A
		$T_C=100^{\circ}\text{C}$	29	-27	
I_{DSM}	Continuous Drain Current ^a	$T_A=25^{\circ}\text{C}$	16	-15	A
		$T_A=70^{\circ}\text{C}$	12	-11	
I_{DM}	Pulsed Drain Current ^b	212	-200	A	
P_D	Power Dissipation ^c	$T_C=25^{\circ}\text{C}$	33	33	W
		$T_C=100^{\circ}\text{C}$	13	13	
P_{DSM}	Power Dissipation ^a	$T_A=25^{\circ}\text{C}$	3	3	W
		$T_A=70^{\circ}\text{C}$	1.9	1.9	
I_{AS}	Avalanche Current ^b L=0.5mH Single Pulse	17	-25	A	
E_{AS}	Avalanche Energy ^b L=0.5mH Single Pulse	72	156	mJ	
T_J	Operation junction temperature	-55~150		$^{\circ}\text{C}$	
T_{STG}	Storage temperature range	-55~150			

➤ Thermal Resistance Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Ratings	Max.	Unit
$R_{\theta JA}$	Junction-to-Ambient Thermal Resistance ^a	41	53	$^{\circ}\text{C}/\text{W}$
$R_{\theta JC}$	Junction-to-Case Thermal Resistance	3.7	4.8	

Note:

- The value of $R_{\theta JA}$ is measured with the device mounted on 1 in² FR-4 board with 2oz.copper, in a still air environment with $T_A=25^{\circ}\text{C}$. The value in any given application depends on the user's specific board design. The current rating is based on the $t \leq 10\text{s}$ thermal resistance rating.
- Repetitive rating, pulse width limited by junction temperature.
- The power dissipation P_D is based on $T_{J(\text{MAX})}=150^{\circ}\text{C}$, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heat sinking is used.



➤ **N-Channel Electrical Characteristics (T_A=25°C unless otherwise noted)**

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250uA	30			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250uA	1.0	1.5	2.5	V
Drain-Source On-Resistance	R _{DS(on)}	V _{GS} = 10V, I _D = 15A		6.2	8.5	mΩ
Drain-Source On-Resistance	R _{DS(on)}	V _{GS} = 4.5V, I _D = 10A		9	13	mΩ
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 30V, V _{GS} = 0V			1	μA
Gate-Source Leak Current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V			±100	nA
Forward Voltage	V _{SD}	V _{GS} = 0V, I _S = 10A		0.8	1.3	V
Gate Resistance	R _G	V _{DS} = 0V, f = 1MHz		2.0		Ω
Input Capacitance	C _{ISS}	V _{DS} = 15V, V _{GS} = 0V, f = 1MHz		1910		pF
Output Capacitance	C _{OSS}			242		
Reverse Transfer Capacitance	C _{RSS}			209		
Total Gate Charge	Q _G	V _{GS} = 10V, V _{DS} = 15V, I _D = 20A		17		nC
Gate to Source Charge	Q _{GS}			5		
Gate to Drain Charge	Q _{GD}			7.5		
Turn-on Delay Time	T _{D(ON)}	V _{GS} = 10V, V _{DS} = 15V, R _L = 1Ω, R _G = 3Ω		8.4		ns
Rise Time	T _r			8.7		
Turn-off Delay Time	T _{D(OFF)}			26		
Fall Time	T _f			9		
Diode Recovery Time	T _{rr}	I _F =20A, di/dt=100A/us		53		ns
Diode Recovery Charge	Q _{rr}	I _F =20A, di/dt=100A/us		39		nC




➤ **P-Channel Electrical Characteristics (T_A=25°C unless otherwise noted)**


Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = -250uA	-30			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250uA	-1.0	-1.8	-2.5	V
Drain-Source On-Resistance	R _{DS(on)}	V _{GS} = -10V, I _D = -15A		8	13	mΩ
Drain-Source On-Resistance	R _{DS(on)}	V _{GS} = -4.5V, I _D = -10A		10	20	mΩ
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -30V, V _{GS} = 0V			-1	μA
Gate-Source Leak Current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V			±100	nA
Forward Voltage	V _{SD}	V _{GS} = 0V, I _S = -10A		-0.8	-1.3	V
Gate Resistance	R _G	V _{DS} = 0V, f = 1MHz		2.8		Ω
Input Capacitance	C _{ISS}	V _{DS} = -15V, V _{GS} = 0V, f = 1MHz		3400		pF
Output Capacitance	C _{OSS}			490		
Reverse Transfer Capacitance	C _{RSS}			360		
Total Gate Charge	Q _G	V _{GS} = -10V, V _{DS} = -15V, I _D = -20A		17		nC
Gate to Source Charge	Q _{GS}			2.3		
Gate to Drain Charge	Q _{GD}			3.1		
Turn-on Delay Time	T _{D(ON)}	V _{GS} = -10V, V _{DS} = -15V, R _L = 1Ω, R _G = 3Ω		8.2		ns
Rise Time	T _r			9.7		
Turn-off Delay Time	T _{D(OFF)}			51		
Fall Time	T _f			24		
Diode Recovery Time	T _{rr}	I _F = -20A, di/dt = -100A/us		57		ns
Diode Recovery Charge	Q _{rr}	I _F = -20A, di/dt = -100A/us		32		nC




➤ N-Channel Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current and Gate Voltage



On-Resistance vs. Gate-to-Source Voltage




On-Resistance vs. Junction Temperature




Safe Operating Area vs. Junction-to-Ambient




➤ P-Channel Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current and Gate Voltage



On-Resistance vs. Gate-to-Source Voltage




On-Resistance vs. Junction Temperature



Safe Operating Area vs. Junction-to-Ambient

➤ Package Information



Dimensions In Millimeterer			
Symbol	MIN	TYP	MAX
A	0.90	1.00	1.10
A1	0.00	0.03	0.05
A2	0.254 REF		
b	0.25	0.30	0.35
D	4.80	4.90	5.00
D1	1.60	1.70	1.80
E	5.90	6.00	6.10
E1	5.65	5.75	5.85
E2	3.38	3.48	3.58
e	1.27 BSC		
K	0.55	0.60	0.65
K1	1.35 REF		
L	0.55	0.60	0.65
L1	0.10	0.13	0.16



DISCLAIMER

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICIENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.