



Silicon Carbide Schottky Diode

➤ Features

VR	IF	VF
1200V	10A	1.5V

➤ Description

- 1200V Schottky Rectifier
- High Frequency Operation
- Extremely Fast Switching
- Positive Temperature Coefficient on V_F




➤ Applications

- Power Supplies
- Power Factor Correction
- Motor Drives

➤ Ordering Information

Device	Package	Shipping
SSC12K10AT2	TO247-3L	0.3K/Box

➤ Pin Configuration



Marking

(XXXX: Year/Week)



➤ **Absolute Maximum Ratings**(TA=25°C unless otherwise noted)

Symbol	Parameter		Ratings	Unit
V_{RRM}	Repetitive Peak Reverse Voltage		1200	V
V_{RSM}	Surge Peak Reverse Voltage		1200	V
V_{DS}	DC Blocking Voltage		1200	V
I_F	Continuous Forward Current	$T_C=150^{\circ}\text{C}$	10	A
I_{FRM}	Repetitive Peak Forward Surge Current ^A		50	A
I_{FSM}	Non-Repetitive Peak Forward Surge Current ^A		95	A
$I_{F\text{ MAX}}$	Non-Repetitive Peak Forward Surge Current ^B		600	A
P_{TOT}	Power Dissipation	$T_C=25^{\circ}\text{C}$	153	W
$T_J\ T_{STG}$	Operating Junction and Storage Temperature		-55~+175	°C

➤ **Thermal Resistance Ratings**(TA=25°C unless otherwise noted)

Symbol	Parameter	Ratings	Unit
$R_{\theta JC}$	Thermal Resistance Junction-to-Case	0.98	°C/W

Note:

A. $T_C=25^{\circ}\text{C}$, $t=10\text{ms}$, Half Sine Wave;

B. $T_C=25^{\circ}\text{C}$, $t=10\mu\text{s}$, Pulse;







SSC12K10AT2

➤ **Electronics Characteristics**(TA=25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Typ.	Max.	Unit
V _F	Forward Voltage	IF=10A TJ=25°C IF=10A TJ=175°C	1.5 2.2	1.8 3	V
I _R	Reverse Current	VR=1200V TJ=25°C VR=1200V TJ=175°C	10 20	50 100	uA
Q _C	Total Charge	VR=400V IF=10A TJ=25°C	50		nC
C	Total Capacitive	VR=0V TJ=25°C f=1MHz VR=400V TJ=25°C f=1MHz VR=800V TJ=25°C f=1MHz	610 46 36		pF
E _C	Capacitance Stored Energy	VR=800V	25		uJ




➤ **Typical Characteristics**(TA=25°C unless otherwise noted)





➤ Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	4.850	5.150	0.191	0.200
A1	2.200	2.600	0.087	0.102
b	1.000	1.400	0.039	0.055
b1	2.800	3.200	0.110	0.126
b2	1.800	2.200	0.071	0.087
c	0.500	0.700	0.020	0.028
c1	1.900	2.100	0.075	0.083
D	15.450	15.750	0.608	0.620
E1	3.500 REF		0.138 REF	
E2	3.600 REF		0.142 REF	
L	40.900	41.300	1.610	1.626
L1	24.800	25.100	0.976	0.988
L2	20.300	20.600	0.799	0.811
Φ	7.100	7.300	0.280	0.287
e	5.450 TYP		0.215 TYP	
H	5.980 REF		0.235 REF	
h	0.000	0.300	0.000	0.012



DISCLAIMER

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.